Fall Protection Work Plan?

Falls are still one of the leading causes of injury and death at work in many of IHSA's rate groups. In 2013, falls were responsible for 25% of lost-time injuries (LTIs), 45% of critical injuries, and 10 fatalities. Compared with 2012, that represents an 11% increase in the number of LTIs from falls and twice the number of fatalities.

Obviously, more needs to be done to protect workers at heights. As an employer in Ontario, you are legally required to protect workers who are exposed to fall hazards. To help you do this, IHSA has developed a Fall Protection Work Plan. It's a step-by-step guide for controlling fall hazards and is intended to offer guidance and instruction for workers using fall protection. It's easy to follow and will help you choose the best method of fall protection that is available to you under the circumstances.

Recognizing and assessing the fall hazard

The first step is to recognize and assess the fall hazard. Identify any existing and potential hazards before work begins. Assess the likelihood and potential severity of the hazard and prioritize the hazards according to risk (Step 1).

Eliminating the fall hazard

The next step is to try to prevent a fall from happening (Step 2). This could involve:

- relocating the work to a place where the fall hazard does not exist (e.g., building a roof on the ground and hoisting it into place or moving an air-handling unit from near the edge of a roof to the centre)
- delaying the work until permanent safety features can be installed (e.g., permanent guardrails, walls, parapets, or other structural features)
- erecting a guardrail system, which prevents workers from falling off an open edge
- covering floor or roof openings so that workers cannot fall through them

- using an elevated work platform (EWP), that has permanent guardrails
- using a travel-restraint system, which allows workers to travel just far enough to reach the edge but not far enough to fall over.

Controlling the fall hazard

If you can't eliminate the fall hazard, the next-best option (Step 3) is to implement controls such as:

- a fall arrest system, which will stop the fall before any part of the worker can hit the surface or an object below
- a safety net, which is installed around the perimeter of a building or at floor or roof openings to arrest a worker's fall.

By allowing a worker to fall, there is an increased likelihood of injury. Also, if you choose this option, you must have a plan to rescue a suspended worker whose fall has been arrested (Step 7).

Creating the Fall Protection Work Plan

Instructions for creating the Fall Protection Work Plan are listed below.

- The plan is to be prepared by the supervisor and workers (competent persons) most directly involved in the work.
- More than one control or elimination method can be selected for the work. For example, travel restraint can be used when guardrails are being installed.
- The plan should be approved by the management supervisor of the person who prepared it (Step 8).
- The plan should be read by all workers involved in the work. Workers can acknowledge that they have read the requirements and understand their responsibilities under the plan by signing a Worker Sign-off Sheet (Step 9).
- An emergency plan should be developed even if a fall rescue plan is not required.
- If the work situation changes and the Fall Protection Work Plan has to be amended, the changes should be communicated to all workers involved.

Fall Protection Work Plan

Company name	_ Project	
Supervisor in charge	_ Work location	
Estimated start date and duration		
Description of work		
Fall protection equipment		
Manufacturer's reference material		
Step 1: Identify the fall hazard. (Provide a description.)		
Step 2: Try to eliminate the fall hazard.		
Can the work be relocated to a place where a fall hazard does	not exist?	□ N
Can the work be delayed until permanent safety features are in	stalled?	□ N
Can a guardrail system be used? If Yes, consider the following:	□ Y	□ N
☐ Does it meet the strength requirements of O. Reg. 213/	91, s. 26.3?	
☐ Is it no more than 30 cm (12 in) from the edge being p	rotected?	
☐ Has the it been installed according to the manufacture	r's recommendations?	
☐ If it is made of wood, can it resist all loads that a worke	er may subject it to?	
Can floor or roof openings be covered? If Yes, consider the follows:	owing:	□ N
Does the cover meet the strength requirements of O. F		
☐ Is it securely fastened?		
☐ Is it adequately identified as a cover?		
Can an elevated work platform (EWP) be used? If Yes, consider	r the following:	□ N
☐ Is the EWP on a level surface?	g	
☐ Is the surface capable of supporting its load?		
☐ Has the worker received fall protection training and be	en trained in the use of this	
specific EWP?		
Can a travel-restraint system be used? If Yes, consider the follow	wing:	□ N
☐ Is the system set up to prevent the worker from reaching	ng the fall hazard?	
Does the system meet the requirements of O. Reg. 213,	/91, s. 26.4?	
☐ Does the anchor point meet the requirements of O. Re	g. 213/91, s. 26.7?	
Have other fall hazards in the work area been consider to use a fall arrest system.	ed? If not, you may need	
☐ Has the equipment been certified by the Canadian Sta	ndards Association (CSA)?	
☐ Has the equipment and system been inspected before instructions and CSA requirements?	use, as per the manufacturer's	
Can scaffolding or pump jacks be used?	D Y	□ N



Step 3: Take steps to control the fall hazard.

If you choose this option, you must have a fall rescue plan in place and the workers must be trained on it before work begins—it's the law.

the used? If Yes, consider the following: an in place to rescue a suspended worker? (See Step 7.) been trained in fall protection and the specific fall arrest system the up to prevent the worker from hitting an object below? Have other the work area been considered? the system meet the requirements of O. Reg. 213/91, s. 26.6? The point meet the requirements of O. Reg. 213/91, s. 26.7? Interpretation of the lifeline is at a 90° angle from the edge? The protection and the specific fall arrest system and the specific	□ Y	□ N
to been trained in fall protection and the specific fall arrest system tup to prevent the worker from hitting an object below? Have other e work area been considered? Lest system meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.7? Lest point meet the requirements of O. Reg. 213/91, s. 26.7? Lest point meet the requirements of O. Reg. 213/91, s. 26.7? Lest point meet the requirements of O. Reg. 213/91, s. 26.7? Lest point meet the requirements of O. Reg. 213/91, s. 26.7? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.7? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements of O. Reg. 213/91, s. 26.6? Lest point meet the requirements per lest point meet the requirements per lest point meet the requirements per lest point meet the requirement meet the requirement meet t		
t up to prevent the worker from hitting an object below? Have other e work area been considered? est system meet the requirements of O. Reg. 213/91, s. 26.6? point meet the requirements of O. Reg. 213/91, s. 26.7? int located so that the lifeline is at a 90° angle from the edge? orker fell, they could swing and hit a wall or column or the lifeline is slid across the edge.		
est system meet the requirements of O. Reg. 213/91, s. 26.6? point meet the requirements of O. Reg. 213/91, s. 26.7? int located so that the lifeline is at a 90° angle from the edge? orker fell, they could swing and hit a wall or column or the lifeline slid across the edge. lifeline systems been engineered? Have they been installed		
r point meet the requirements of O. Reg. 213/91, s. 26.7? int located so that the lifeline is at a 90° angle from the edge? orker fell, they could swing and hit a wall or column or the lifeline slid across the edge. lifeline systems been engineered? Have they been installed		
int located so that the lifeline is at a 90° angle from the edge? orker fell, they could swing and hit a wall or column or the lifeline slid across the edge. lifeline systems been engineered? Have they been installed		
orker fell, they could swing and hit a wall or column or the lifeline slid across the edge. Iifeline systems been engineered? Have they been installed		
st equipment been certified by the CSA?		
ent or system been inspected before use, as per the manufacturer's CSA requirements?		
? If Yes, consider the following:	□ Y	□ N
its meet the requirements of of O. Reg. 213/91, s. 26.8? nets been installed according to the manufacturer's instructions?		
e used? If Yes, describe them:	□ Y	□ N
	CSA requirements? If Yes, consider the following: Ian in place to rescue a suspended worker? (See Step 7.) Its meet the requirements of of O. Reg. 213/91, s. 26.8? In the seen installed according to the manufacturer's instructions? In the seen inspected according to the manufacturer's instructions? If Yes, describe them: It is a requirements?	? If Yes, consider the following: lan in place to rescue a suspended worker? (See Step 7.) ets meet the requirements of of O. Reg. 213/91, s. 26.8? nets been installed according to the manufacturer's instructions? nets been inspected according to the manufacturer's instructions?



Step 5: Describe the system setup or work procedures.

Rescue equipment: ______ Rescuers' names: _____



Step 6: Calculate the fall clearance.



Step 7: Create a fall rescue plan to rescue a suspended worker.



Step 8: Get approvals.

Prepared by .

Approved by ______ Date approved _____



Step 9: Create a Worker Sign-off Sheet.

Workers need to acknowledge that they have read the requirements and understand their responsibilities under the Fall Protection Work Plan.